

# Walsh Tundra

## 4000 Series Vinyl Window & Door Systems

### 4000 Series

### Single Hung Single Slide



### 4100 SINGLE HUNG

WINDOW TYPE	GLASS PACKAGE	U-VALUE	SHCC	VISIBLE TRANSMITTANCE	CONDENSATION RESISTANCE
NO FOAM	#1	.31	.34	.59	.58
FOAM	#1	.29	.34	.59	.58
NO FOAM	#2	.30	.22	.53	.58
FOAM	#2	.28	.22	.53	.58
GLASS PACKAGE					
TUNDRA #1	CLEAR/ARGON/LOE 272		3/4" IG LOE SURFACE #2		
TUNDRA #2	LOE 366/ARGON/CLEAR		3/4" IG LOE SURFACE #2		

#### Thermal Performance Package #1

3/4" thick dual pane unit made of one LoE 272 and one clear pane with Cardinal XLEdge Spacer and argon fill.

- ▶ Increased condensation resistance.
- ▶ Savings on heating and cooling costs.

#### Thermal Performance Package #2

3/4" thick dual pane unit made of one LoE 366 and one clear pane with Cardinal XLEdge Spacer and argon fill.

- ▶ High performance glass.
- ▶ Better U-value for lower heating costs.
- ▶ Less solar heat gain lowers cooling cost.
- ▶ Cut in fading transmission.

### Single Hung Features

- ▶ All welded frame and sash.
- ▶ Sloped sill designed for efficient water evacuation.
- ▶ Full complement of accessory profiles.
- ▶ 3 1/4" frame width ideal for replacement installations.
- ▶ Exterior glazed sash.
- ▶ Stainless steel constant force balancers.
- ▶ Frame options: Replacement frame, regular nail fin frame, J-fin designed with brick mold accent frame.
- ▶ Maximum glass thickness of 3/4".
- ▶ Optimum designed aluminum sash reinforcement.
- ▶ Dual weatherstripping.
- ▶ Multi chambered vinyl profiles for thermal efficiency.
- ▶ Up to DP50 performance levels.
- ▶ Interlocks designed for ease of operation and positive engagement.



# 4200 Single Slide



4000 Series Windows

Single Hung  
Single Slide

## 4200 SINGLE SLIDE

WINDOW TYPE	GLASS PACKAGE	U-VALUE	SHCC	VISIBLE TRANSMITTANCE	CONDENSATION RESISTANCE
NO FOAM	#1	.30	.34	.58	.58
FOAM	#1	.29	.34	.58	.58
NO FOAM	#2	.29	.22	.52	.59
FOAM	#2	.28	.22	.52	.59

### GLASS PACKAGE

TUNDRA #1	CLEAR/ARGON/LOE 272	3/4" IG LOE SURFACE #2
TUNDRA #2	LOE 366/ARGON/CLEAR	3/4" IG LOE SURFACE #2



### Optional Foam Fill Sash & Frame

- ▶ The foam filled dead air chambers and non-conductive PVC improves insulation.
- ▶ Neopor foam insulates up to 8% better than dead air space.




### Available colors for windows, doors and accessories

Due to the limitations of the printing process colors shown may vary. Please call for actual color samples if needed.



Black Laminate Exterior/  
White Interior



White

## Single Slide Features

- ▶ All welded frame and sash.
- ▶ Full complement of accessory profiles.
- ▶ 3 3/4" frame width ideal for replacement installations.
- ▶ Exterior glazed equal glass sash.
- ▶ Tandem brass rollers for enhanced operation.
- ▶ Frame options: Replacement frame, regular nail fin frame, J-fin designed with brick mold accent frame.
- ▶ Maximum glass thickness of 3/4".
- ▶ Optimum designed aluminum sash reinforcement.
- ▶ Dual weatherstripping.
- ▶ Multi chambered vinyl profiles for thermal efficiency.
- ▶ Up to DP50 performance levels.
- ▶ Interlocks designed for ease of operation and positive engagement.
- ▶ Operating panel lifts out for cleaning